



NetBox VR Quatro


Overview

The NetBox™ VR Quatro system combines the power of the NetBox access control system with the NetVR™ video management system. Access control, event monitoring, video surveillance and video forensics are available through the NetBox and NetVR web browser interfaces, Magic Monitor® client or Mobile Security Professional® mobile app.

The NetBox VR Quatro system is designed to be convenient and economical to install and maintain. Sites with up to eight recorded cameras and eight full access control points can be handled using a single wall mount enclosure. The appliance includes four slots for standard LenelS2 application blades, including access control, supervised inputs, relay outputs and analog temperature monitoring.

Program and system data is stored on a solid-state disk, while video streams to the internal hard disk. The NetBox VR Quatro system is available with 2TB or 4TB of replaceable video storage, providing storage typically in the 30 – 120 day range. Stored video is easily searched using Magic Monitor Forensics.

The NetBox VR Quatro system is ideal for stand-alone installations or as a member of a NetBox Global distributed network where it can be locally or remotely managed.



Easily search, review and catalog video with Magic Monitor Forensics.

Key Features

Access Control

- **Portals:** Supports up to 8 doors or other access points
- **Event and Alarm Monitoring:** Includes comprehensive event logging, notification and escalation
- **Threat Level Management:** Provides configurable system status and response actions such as system lock downs
- **Person Record Management:** Maintains detailed, credential-driven user records and access history
- **Reporting:** Offers pre-defined and custom reports

Video Management

- **Cameras:** Supports up to 8 IP cameras
- **Real-Time Surveillance:** Allows for live video tours and on-screen PTZ controls
- **Forensic Search:** Locates recorded video of interest with a single click and saves it to the case library
- **Storage:** Supports either 2TB or 4TB media drive

System

- **All-In-One System:** Provides access control and video management system capabilities in a single, converged system
- **Web Interface:** Delivers browser-based, unified system management and administration
- **Solid State Design:** Extends product lifecycle, lowering total cost of ownership
- **Blade Support:** Houses up to four LenelS2 application blades for access control, inputs, outputs and temperature probes
- **Mobile Apps:** Enables mobile security management, mobile credentials and more



Specifications – NetBox VR Quatro

Access Control

Cardholders	20,000
Access Levels	512
Unique User Roles	Unlimited
Simultaneous Users	2
Time Specifications	512
Portal Capacity	8
LenIS2 Application Blade Support	4 application blades for access control, inputs, outputs and temperature probes
Maximum Inputs/Outputs	32/32
Online Transactions	40,000,000

Video Management

IP Camera Streams	8
IP Camera Resolution	IP camera dependent
IP Camera Frame Rate	IP camera dependent
Compression Type	H.264 or H.265 (camera dependent)

Appliance

Video Storage	2TB or 4TB media drive
Processor	Intel® N3350
Memory (RAM)	8GB
Operating System	Ubuntu Linux
OS/Application Storage	256GB SSD
Ethernet Ports	1
Max Video Throughput (Aggregate Inbound + Outbound)	75 Mbps
MTBF	107,071
Chassis	Wall mount
Dimensions (H, W, D)	13in x 13in x 8.5in (330mm x 330mm x 216mm)

Appliance (continued)

Weight	9.7 lbs (4.4 kg) maximum
Operating Temperature	32° – 95° F (0° – 35° C)
Storage Temperature	-4° – 158° F (-20° – 70° C)
Operating Environment	Humidity 85%, Non-condensing 35° C
AC Input	100 – 240 VAC , 50/60 Hz, 1.7A
BTU Maximum	1,075 per hour
Regulatory Approvals	UL, CE, FCC, RoHS
Warranty ¹	2 years, hardware 1 year, software

Client Requirements

Operating System	Any; for badging use Windows® 10
Browser ²	Chrome™, Internet Explorer®, Firefox® and Safari®
Processor	Intel Core™ i3 or higher
Memory	4GB
Hard Drive	100GB minimum


Integrations³

Concurrent LenIS2 Client Connections (NetBox, Magic Monitor, Mobile Security Professional)	10
Access Control	Allegion, ASSA ABLOY, dormakaba & Mercury
Intrusion	Bosch, DMP, API-Based
	2TB, 8 IP Cameras
S2-QUATROVR-2TB	4TB, 16 IP Cameras
S2-QUATROVR-4TB	Single camera license
S2-VR-1C	

¹ Please contact your LenIS2 authorized Value-Added Reseller for complete warranty details.

² Refer to the latest Release Notes for browser version compatibility.

³ For additional information, please contact us.



Schematic only. Not a network diagram.



For more information, please visit lenels2.com.

Specifications subject to change without notice.
 © 2014, 2022 All Rights Reserved. All trademarks and service marks referred herein are property of their respective owners. LenelS2 is a part of Carrier.

S2102821

